

NERO-6MRN151D

6" - Midrange - Neo - 360W - 98dB

AUDIENCE

- Cast aluminium chassis
- High grade neodymium magnet
- CCAW voice coil for reduced moving mass
- Proprietary cone paper material with graphite
- Minimum damping fiber glass voice coil former
- Flat foam surround for best midrange reproduction
- Shorting ring in motor system for reduced distortion



Dimensions & Weight

Overall Diameter	185 mm (7.28 in)
Bolt Circle Diameter	170 mm (6.69 in)
Baffle Cutout Diameter	147.5 mm (5.81 in)
Mounting Depth	73.5 mm (2.89 in)
Flange and Gasket Thickness	5.0 mm (0.19 in)
Net Weight	1.6 Kg (3.52 lb)
Shipping Box	194 x 194 x 112 mm (7.64 x 7.64 x 4.41 in)
Gross Weight	1.9 Kg (4.19 lb)

Recone Kit

N/A

NOTES :

- (1) AES standard, test mode with continuous pink noise signal (6 dB crest factor; 2 hours) within the Fo to 10Fo power calculated on rated minimum impedance. Loudspeaker in free air
- (2) Maximum power is defined as 3dB greater than nominal power
- (3) Measured average within the frequency range (500Hz - 5kHz)
- (4) $X_{max} = ((\text{Winding depth} - \text{magnetic gap depth})/2) + (\text{magnetic gap depth}/3)$
- (5) Maximum excursion (p-p) before permanent damage
- (6) T/S parameters measured on drive units that are broken in

Specs :

Nominal Impedance	8 Ohm
Minimum Impedance	5.6 Ohm
AES Power Handling (1)	180 W
Maximum Power Handling (2)	360 W
Sensitivity (2.83V/1m) (3)	98 dB
Frequency Range	230 - 10500 Hz
Voice Coil Diameter	49.5 mm (2 in)
Winding Material	Copper clad aluminium
Former Material	Till
Winding Depth	8.85 mm
Magnetic Gap Depth	6 mm (0.24 in)
Flux Density	1.74 T
Magnet	Neodymium
Basket Material	Aluminium die cast
Demodulation	Aluminium shorting ring
Cone Surround	Flat foam
NET Air Volume filled by driver	0.72 liters
Spider Profile	Single constant height waves
Weather Resistant	Yes

Thiele Small Parameters

Fs	230 Hz
Re	5.6 Ohm
Qes	0.58
Qms	2.65
Qts	0.48
Vas	0.8 liters
Sd	136.8 cm ²
Xmax (4)	3.43 mm
Xdamage (5)	8 mm
Mms	14.6 g
Bl	14.5 Tm
Le	0.17 mH
Cms	0.03 mm/N
Rms	8.21 Kg/s
Eta Zero	1.8 %
EBP	409

